
## KEMET Part Number: T541X336M050AH6710

(04052-064B)



Tantalum, Polymer Tantalum, COTS Multi-Anode, T541\_COTS, 33 uF, 20%, 50 V, 7343, SMD, Polymer, Molded, COTS, Multi-Anode, Low ESR, N/A, 75 mOhms, Height Max = 4.3mm



Dimensions	
Footprint	7343
L	7.3mm +/-0.3mm
W	4.3mm +/-0.3mm
Н	4mm +/-0.3mm
Т	0.13mm REF
S	1.3mm +/-0.3mm
F	2.4mm +/-0.1mm
Α	3.8mm MIN
В	0.5mm +/-0.15mm
E	3.5mm REF
G	3.5mm REF
Р	1.7mm REF
R	1mm REF
Х	0.1mm +/-0.1mm

Packaging Specifications		
Weight:	410.89 mg	
Packaging:	T&R, 178mm	
Packaging Quantity:	500	

General Information		
Dielectric:	Polymer Tantalum	
Style:	SMD Chip	
Series:	T541_COTS	
Description:	SMD, Polymer, Molded, COTS, Multi-Anode, Low ESR	
Features:	Non-Combustible, Multiple Anode, Low ESR, COTS	
RoHS:	No	
Termination:	Solder Coated	
Approvals:	DLA Drawing 04052	
Notes:	In polarity stripe, at KEMET's option, type may be indicated: no symbol = Standard (or low leakage) MnO2 tantalum chip, O = LowESR T494, R = Low ESR T495, F = Fused T496, HT = 150C rated T498 (or B45196P, B45198P), H = 175C rated T499, H2 = 200C rated T50	

Specifications	
Capacitance:	33 uF
Capacitance Tolerance:	20%
Voltage DC:	50 VDC (85C), 33.5 VDC (125C)
Temperature Range:	-55/+125C
Dissipation Factor:	10% 120Hz 25C
Failure Rate:	N/A
Resistance:	75 mOhms (100kHz 25C)
Current:	1897 mAmps (100kHz 45C)
Leakage:	165 uAmps (5min 25C)
Testing and Reliability:	10 Cycles Surge Current Testing At -55C +0C/-5C And +85C +/-5C After Voltage Aging



Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.